



DIGITECH TURBINES



**OLIEMOLENSTRAAT 5
6343PW, WEUSTENRADENETHERLANDS
TEL +31-(0)45-4059000
WWW.DIGITECH.NL**

Thank you for purchasing our Landing gear..
Here are a few tips about correctly using and mounting our landing Gears.

Filling / Inflating / Deflating

1. all our tyres are inflatable and deflatable here is how to do it:
2. In the rim you see a small 3mm hole , here you fill air inside the tyre , it Works due to a o-ring that is placed on the inside of the rim , it will let air in but not out..
3. Deflating : loosen all screws to let air escape..
4. Min and max size **WARNING!! Do no OVERPRESSURE!!** , you can measure the tyre for correct pressure max size is 83MM!!
5. For filling them it is best you use a small tip from a ZAP CA Bottle cut of the First 3mm , put a festo 4mm tube in from the other side and you have a filling nipple..



Mounting Oleo,s correctly

It is very important to Mount them correctly overtightening is not the correct way , and can cause a none working gear , difficult to retract!

1. put a few drops of loctite onto the part that goes inside the retract , fasten it but do NOT overdo it , make sure the trunion Block bends
2. Aldo correct mounting inside you model is important , if the mounting rails are not equally mounted , and you fasten the gear , it can bend and cause a none or difficult working retract



Maintenance : only use TEFLON grease or oil to lubricate , once a month put a few drops thru your filling valve to lubricate everything.

